



I/O module for IoT application

DigiRail OEE



DigiRail OEE is an I/O module for IoT application designed for OEE (Overall Equipment Effectiveness) and MES (Manufacturing Execution System) industrial systems.



Reliable and stable connectivity for data transmission

DigiRail OEE has the main industrial approvals, in order to assure monitoring reliability in harsh environments. Its internal memory buffer capability grants data retention and integrity in an eventual downlink, keeping the data logging seamlessly.



Native compatibility with main cloud providers

Provided with secure MQTT protocol, **DigiRail OEE** transmits data natively to Google Cloud, Microsoft Azure, Amazon AWS, NOVUS Cloud, or any other compatible IoT cloud platform.



Intuitive software designed for easy commissioning

NXperience software provides a user-friendly configuration interface, allowing input simulation and output forcing, locally through USB port and remotely through Modbus TCP.



Allows remote settings and diagnosis

System diagnosis and maintenance become very easy thanks to the remote configuration and viewing functions. **DigiRail OEE** allows to send MQTT and Modbus TCP commands to read status and to set device parameters.



- Inputs:**
- 6 digital
 - 2 analog
- Outputs:**
- 2 digital
- Communication interface:**
- Ethernet: 10/100 Mb/s, IEEE standard 802.3 or Wi-Fi 802.11 b/g/n 2.4 GHz

NAME	SIMBOL	STATUS	DESCRIPTION
STATUS		Off	Device off
		On	Device on
		Blinking	Device in firmware actualization module
INDICATOR OF WI-FI CONNECTION / ETHERNET		On	The connection has been established
		Blinking	Data is being transmitted
		Off	The connection hasn't been established
INDICATOR OF CONNECTION WITH THE MQTT BROKER		On	The connection has been established
		Blinking	Data is being transmitted
		Off	The connection is disabled or failed to initialize

Technical Specifications

Inputs	6 digital, 2 analog	Communication interface	USB Ethernet: 10/100 Mb/s, IEEE standard 802.3 or Wi-Fi 802.11 b/g/n 2.4 GHz RS485
Outputs	2 digital	Software	NXperience
Analog signals	0-5 V, 0-10 V, 0-20 mA and 4-20 mA	Power supply	Voltage: 10 Vdc to 36 Vdc
Digital signals	NPN, PNP, and dry contact	Wi-Fi model	Typical consumption: 70 mA @ 24 V Maximum consumption: 160 mA @ 12 V
Analog input Impedance	mA: 15 Ω + 1.5 V V: 1 MΩ	Ethernet model	Typical consumption: 50 mA @ 24 V Maximum consumption: 120 mA @ 12 V
Analog Resolution	Analog Inputs: 15 bits (65000 levels)	Operation Conditions	Temperature: -20 to 60°C (-4 to 140°F) Humidity: 5 to 95% RH, non-condensing
Digital input Features	Logical level "0" < 0.5 V Logical level "1" > 3 V Maximum voltage: 30 V Input impedance: 270 kΩ Input current: @ 30 Vdc (typical) 0.15mA Maximum frequency (square wave): Dry contact: 10 Hz PNP: 3 kHz NPN: 3 kHz	Battery	CR2032 for internal clock retention
Minimum pulse duration	Dry contact: 50 ms PNP: 150 us NPN: 150 us	Assembly	DIN rail or screw mounting
Digital output characteristics	2 NPN digital outputs Maximum current that can switch the output: 700 mA	Degree of Protection	IP20
		Enclosure	ABS + PC